

Article No.: Print date: Version: 10-361-099 17.09.2014 1.2

RELAFLOOR 361 2K-EP -B-Revision date: 17.09.2014 Issue date: 25.08.2014

999998 EN Page 1 / 7

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifiers

Article No. (manufacturer/supplier) Identification of the substance or mixture 10-361-099 RELAFLOOR 361 2K-EP -B-Hardener, Component B

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses:** Hardener for 2 component epoxy resins or coatings

## $1.3. \ \ \, {\rm Details}$ to the supplier providing the material safety data sheet

#### Producer:

## FEYCOLOR GmbH

Maxhuettenstraße 6, 93055 Regensburg, Germany

Tel.: +49 (0) 941/ 60497-0 Fax.: +49 (0) 941/ 60497-30 info@feycolor.com www.feycolor.com

Office hours: Monday - Thursday: 08:00 - 12:00 and 13:00 - 16:00 Friday: 08:00 - 12:00

Department responsible for information:

Hazardous material management: sd@feycolor.com

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification according to Directive 67/548/EEC or 1999/45/EC

This mixture is classified as hazardous according to 1999/45/EC.

Harmful

Corrosive

Xn; R20/22	
C; R34	
R43	
R52-53	

Harmful by inhalation and if swallowed. Causes burns. May cause sensitization by skin contact. Harmful to aquatic life. May cause long-term adverse effects in the aquatic environment.

### 2.2. Label elements

Labelling (67/548/EEC or 1999/45/EC)

-----

C Corrosive

Hazard statements	
20/22	Harmful by inhalation and if swallowed.
34	Causes burns.
43	May cause sensitization by skin contact.
52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Precautionary stater	nents
24	Avoid contact with skin.
26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
38	In case of insufficient ventilation, wear suitable respiratory equipment.
45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
51	Use only in well-ventilated areas.
61	Avoid release to the environment. Refer to special instructions/safety data sheet.
23	Do not breathe vapour.



Article No.: 10-361-099 17.09.2014 1.2

RELAFLOOR 361 2K-EP -B-Revision date: 17.09.2014 Issue date: 25.08.2014

999998 EN Page 2 / 7

contains:

3-aminomethyl-3,5,5-trimethylcyclohexylamine m-Xylylendiamine benzyl alcohol Phenol, styrolisiert

Special provisions concerning the labelling of certain mixtures n.a.

Print date:

Version:

#### 2.3. Other hazards

## **SECTION 3: Composition / information on ingredients**

#### 3.2. Mixtures

#### Product description / chemical characterization

Description Solvent free polyamide resin

#### **Hazardous ingredients**

EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification	Remark
202-859-9	01-2119492630-38	
100-51-6	benzyl alcohol	25 - 50
603-057-00-5	Acute Tox. 4 H332 / Acute Tox. 4 H302	
220-666-8	01-2119514687-32	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	20 - 25
612-067-00-9	Acute Tox. 4 H312 / Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens.	
	1 H317 / Aquatic Chronic 3 H412	
216-032-5	01-2119480150-50	
1477-55-0	1,3-Bis(aminomethyl)benzene	5 - 10
	Skin Corr. 1B H314 / Acute Tox. 4 H332 / Acute Tox. 4 H302 / Skin Sens.	
	1 H317 / Aquatic Chronic 3 H412	
262-975-0	02-2119629611-43	
61788-44-1	Styrenated phenol	5 - 10
	Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411	

Classification according to Directive 67/548/EEC or 1999/45/EC DEACUN

EC NO.	REACH NO.	
CAS No.	Chemical name	Wt %
INDEX No.	classification	Remark
202-859-9	01-2119492630-38	
100-51-6	benzyl alcohol	25 - 50
603-057-00-5	Xn; R20/22	
220-666-8	01-2119514687-32	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	20 - 25
612-067-00-9	Xn; R21/22 / C; R34 / R43 / R52-53	
216-032-5	01-2119480150-50	
1477-55-0	m-Xylylendiamine	5 - 10
	C; R35 / Xn; R20/22 / R43 / R52-53	
262-975-0	02-2119629611-43	
61788-44-1	Phenol, styrolisiert	5 - 10
	Xi; R38 / R43 / N; R51-53	
A ddition of inform	ation	

#### Additional information

Full text of R-phrases: see section 16.

Full text of H-phrases: see section 16.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.



 Article No.:
 10-361-099

 Print date:
 17.09.2014

 Version:
 1.2

RELAFLOOR 361 2K-EP -B-Revision date: 17.09.2014 Issue date: 25.08.2014

999998 EN Page 3 / 7

#### After inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do not induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. Indication of any immediate medical attention and special treatment needed

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

#### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3. Special protective equipment for firefighters:

Provide a conveniently located respiratory protective device.

#### Additional information

Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

#### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

#### 6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition"



 Article No.:
 10-361-099

 Print date:
 17.09.2014

 Version:
 1.2

RELAFLOOR 361 2K-EP -B-Revision date: 17.09.2014 Issue date: 25.08.2014

999998 EN Page 4 / 7

hazards due to electrostatic charges (BGR 132)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

## Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Occupational exposure limit values:

n.a.

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### **Occupational exposure controls**

#### **Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

#### **Dand protection**

For prolonged or repeated handling the following glove material must be used: solventresistant Latex gloves

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye protection

Wear closely fitting protective glasses in case of splashes.

#### **Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

#### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance: Physical state Colour Odour	see productname typical			
Safety relevant basis data		Unit	Method	Remark
Flash point (°C):	100	°C		
Ignition temperature in °C:	300	°C		
lower explosion limit:	n.a.			
Upper explosion limit:	n.a.			
Vapour pressure at 20 °C:	n.a.			
Density at 20 °C: 20	1,03	g/cm³		
Water solubility (g/L):	partly soluble			
pH value at 20 °C: 20	n.a.			
Viscosity at 20 °C: 20	190	mPa∙s		
Solvent separation test (%):	< 3	%		

		according to	Regulation (EU) N	o 453/2010	
	EYCOLOR®				
		Article No.: Print date: Version:	10-361-099 17.09.2014 1.2	RELAFLOOR 361 2K-EP -B- Revision date: 17.09.2014 Issue date: 25.08.2014	999998 EN Page 5 / 7
	Solid content (%):		100 W	't %	
	solvent content:		0.00 \	/+ 0/	
	Organic solvents: Water:		0,00 M 0,00 M		
9.2.	Other information				
	SECTION 10: Stability a	nd reactivity			
10.1.	Reactivity				
10.2.	<ul> <li>Chemical stability</li> <li>Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.</li> </ul>				
10.3.	Possibility of hazardous re Keep away from strong acid		and strong oxidizing a	agents to avoid exothermic reactions.	
10.4.				nd handling. Further information on correctors	ect storage: refer to
10.5.	Incompatible materials				
10.6.	Hazardous decomposition Hazardous decomposition b smoke, nitrogen oxides.		orm with exposure to	high temperatures, e.g.: carbon dioxide	, carbon monoxide,
	SECTION 11: Toxicolog	ical informatio	on		
	No data on preparation itsel	f available.			
11.1.	Information on toxicologic	al effects			
	Acute toxicity				
	Toxicological data are not available.				
	Irritant and corrosive effects				
	Toxicological data are not available.				
	Sensitisation				
	Toxicological data are not available.				
	Specific target organ toxicity				
	Toxicological data are not available.				
	Aspiration hazard Toxicological data are not a	vailable			
	CMR effects (carcinogenic		ty and toxicity for re	production)	
	Toxicological data are not a				
	Practical experience/huma				
	Other observations: Repeated or prolonged cont	act with the prep		moval of natural fat from the skin resultir cause eye irritation and reversible dama	
	Overall Assessment on CM	MR properties			
	The ingredients in this prepa 67/548/EEC.	aration do not me	eet the criteria for clas	sification as CMR category 1 or 2. accor	ding to
	There is no information available method of the Dangerous P			preparation has been assessed followir has not been classified.	ng the conventional
	SECTION 12: Ecologica	l information			
12.1.	overall evaluation There is no information avai Do not allow to enter into su Toxicity No information available.				



Article No.: Print date: Version: 10-361-099 17.09.2014 1.2 RELAFLOOR 361 2K-EP -B-Revision date: 17.09.2014 Issue date: 25.08.2014

999998 EN Page 6 / 7

## Long-term Ecotoxicity

Toxicological data are not available.

- 12.2. **Persistence and degradability** Toxicological data are not available.
- 12.3. **Bioaccumulative potential** Toxicological data are not available.

**Bioconcentration factor (BCF)** Toxicological data are not available.

12.4. Mobility in soil Toxicological data are not available.

## 12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Appropriate disposal / Product

#### Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

#### List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or other dangerous substances

#### packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

### **SECTION 14: Transport information**

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

#### 14.1. UN number

2735

14.2.	UN proper shipping name	
	Land transport (ADR/RID):	Amines, liquid, corrosive, n.o.s. (ISOPHORONE DIAMINE)
	Sea transport (IMDG):	AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONE DIAMINE)
	Air transport (ICAO-TI / IATA-DGR):	Amines, liquid, corrosive, n.o.s. (ISOPHORONE DIAMINE)
14.3.	Transport hazard class(es)	
		8
14.4.	Packing group	
		III
14.5.	Environmental hazards	
	Land transport (ADR/RID)	n.a.
	Marine pollutant	n.a.
14.6.	Special precautions for user	
	Transport always in closed upright and safe con	tainers. Make sure that persons transporting

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

### **Additional information**

<b>FEYCOLOR</b> <sup>®</sup>	according to Regulation (EU) No 453/2010			
	Article No.: Print date: Version:	10-361-099 17.09.2014 1.2	RELAFLOOR 361 2K-EP -B- Revision date: 17.09.2014 Issue date: 25.08.2014	999998 EN Page 7 / 7
Land transport (ADR/RI	D)			
tunnel restriction code		E		
Sea transport (IMDG)				
EmS-No.		F-A, S-B		
14.7. Transport in bulk accor not applicable	ding to Annex II o	f MARPOL 73/78 ar	nd the IBC Code	
SECTION 15: Regulat	ory information			
EU legislation	to 1999/13/EC abor 1890-2: 1 D 2369: tion 2004/42/EC (a rduct (cat. nicht anv	ut limitation of emi ppendix II)	ecific for the substance or mixture ssions of volatile organic compounds ( < 1 g/l VOC < 1 g/l VOC 7)/0 g/l (2010).	VOC-guideline).
National regulations	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
Restrictions of occupat Observe employment res	trictions under the		Directive (92/85/EEC) for expectant or nu "juvenile work protection guideline" (94/33	
Other regulations, restr	ictions and prohit	ition regulations		
15.2. Chemical Safety Assess Chemical safety assessm		s in this preparation	were not carried out.	
SECTION 16: Other in	nformation			
Relevant R-and H-phras	ses (Number and f	ull text):		

Relevant R-and H-phrases (Number and full text):							
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.					
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.					
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.					
Skin Corr. 1B / H314	skin corrosion/irritation	Causes severe skin burns and eye damage.					
Skin Sens. 1 / H317	respiratory or skin sensitisation	May cause an allergic skin reaction.					
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.					
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.					
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.					
Xn; R20/22	Harmful	Harmful by inhalation and if swallowed.					
Xn; R21/22	Harmful	Harmful in contact with skin and if swallowed.					
C; R34	Corrosive	Causes burns.					
R43		May cause sensitization by skin contact.					
R52-53		Harmful to aquatic life. May cause long-term					
		adverse effects in the aquatic environment.					
C; R35	Corrosive	Causes severe burns.					
Xi; R38	Irritant	Irritating to skin.					
N; R51-53	Dangerous for the environment	Toxic to aquatic life. May cause long-term					
		adverse effects in the aquatic environment.					

## Additional information

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.